

RANGE COMPOSITION

A range of central hoods with characteristic square shape that goes well with technological hoods, as well as offering sturdiness. This shape allows the container to hold fumes before making them flow to the filters. The range consists of hoods with 6 different lengths (2000, 2400, 2800, 3200, 3600 and 4000 mm) and 2200 mm deep.



EXPORT - E line - 2200 mm 304 AISI CENTRAL HOODS



ZANUSSI
PROFESSIONAL

FUNCTIONAL AND CONSTRUCTION FEATURES


- ◆ Constructed entirely in 304 AISI stainless steel.
- ◆ Labyrinth filters in 304 AISI stainless steel easily removable for cleaning. Labyrinth filters guarantee constant filtration to avoid clogging and protect against fire.

- ◆ Perimetral gutter with drain hole to transfer grease into a 304 AISI container.
- ◆ External panels with upturned edges to avoid injuries.
- ◆ Blind panels in 304 AISI stainless steel for a correct exhaustion.
- ◆ The outlet holes are sized in order to minimize drops in pressure.
- ◆ Pressure gauging for perfect calibration.
- ◆ Condensate collection tray in 304 AISI stainless steel.
- ◆ Eyebolts and screw anchors for ceiling installation.
- ◆ Prearranged for installation of lighting.

| TECHNICAL DATA CHARACTERISTICS | MODELS | | | | | |
|-----------------------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| | EC2220T 642043 | EC2224T 642044 | EC2228T 642014 | EC2232T 642045 | EC2236T 642046 | EC2240T 642047 |
| External dimensions - mm | | | | | | |
| width | 2000 | 2400 | 2800 | 3200 | 3600 | 4000 |
| depth | 2200 | 2200 | 2200 | 2200 | 2200 | 2200 |
| height | 500 | 500 | 500 | 500 | 500 | 500 |
| Air Capacity - mc/h | 5600 | 6700 | 7800 | 8900 | 10000 | 11100 |
| Net weight - kg. | 82 | 92 | 102 | 112 | 121 | 131 |
| INCLUDED ACCESSORIES | | | | | | |
| 304 S/S BLIND PANEL 400X500H MM | 2 | | | | 2 | 2 |
| 304 S/S LABYRINTH FILTER H=500 MM | 8 | 8 | 10 | 12 | 12 | 14 |



| OPTIONAL ACCESSORIES | | | | | | |
|--|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| ACCESSORIES | MODELS | | | | | |
| | EC2220T 642043 | EC2224T 642044 | EC2228T 642014 | EC2232T 642045 | EC2236T 642046 | EC2240T 642047 |
| 27-WATT LIGHTING FIXTURE W/1 LAMP-IP 65 | 680804 | 680804 | | | 680804 | 680804 |
| 36-WATT LIGHTING FIXTURE W/1 LAMP-IP 65 | | | 680805 | 680805 | 680805 | 680805 |
| DRAIN FOR HOODS DIAM. 1/2"(M) WITH PLUG | 640409 | 640409 | 640409 | 640409 | 640409 | 640409 |
| FAN FOR VENTIL HOODS+DUCTED EXTRACT.UNIT | 640748 | 640748 | 640748 | 640748 | 640748 | 640748 |
| SPEED VARIATOR FOR MOTORS UP TO 1.7 KW | 640686 | 640686 | 640686 | 640686 | 640686 | 640686 |



www.zanussiprofessional.com